

## Laserworld CS-24.000RGB FB4

A powerful semi-professional pure diode laser, capable of producing intense standard laser effects such as beams, waves and tunnels, as well as basic graphics. This laser is equipped with an FB4 interface, enabling DMX, ArtNet and stand-alone control, as well as computer control from QuickShow or BEYOND. Perfect for medium to large-scale nightclub installations, indoors or out.

- 24'000 mWRGB pure diode laser system
- Pangolin FB4 interface
- DMX / ArtNet controllable
- Stand-alone mode
- Computer controllable via FB4 interface (requires QuickShow or BEYOND software)
- Basic graphics capability - scanners
- Analog modulation
- Laser beam masking plate on front panel
- 360° mounting bracket
- IP54 enclosure



### DETALLES TÉCNICOS

<b>Potencia Garantizada</b>	24'000 mW
<b>Potencia Rojo</b>	5'500 mW / 638 nm
<b>Potencia Verde</b>	6'500 mW / 520 nm
<b>Potencia Azul</b>	12'000 mW / 450 nm
<b>Espec. del Haz</b>	ca. 6 mm / 1.3 mrad
<b>Escáner</b>	30 kpps @ 8°
<b>Apertura Máx.</b>	50°
<b>Modos de Uso:</b>	FB4, ILDA, DMX, ArtNet
<b>Clase</b>	4

<b>Tipo de Láser</b>	Diodo
<b>Clase IP</b>	IP54
<b>Figuras Básicas</b>	Disponible para descargar
<b>Accesorios</b>	cable de alimentación, manual, interlock, llave
<b>Fuente de Alimentación</b>	85 V - 250 V AC, 50/60 Hz
<b>Consumo Eléctrico</b>	300W
<b>Tamaño</b>	400 x 240 x 220 mm
<b>Peso</b>	19.0 kg
<b>EAN / MPN</b>	7640144996079FB4



\*Debido a la tecnología de corrección óptica avanzada utilizada en nuestros sistemas láser, la potencia óptica de cada color dentro de los módulos láser instalados puede diferir ligeramente de la especificación de los respectivos módulos láser. Divergencia FWHM media según modelo.